

Models	T3100	T3200	T3300	T3400	T3600	T3700	T3800
	Capacity Optimized	Balanced	Performance Optimized	Max Performance & Capacity	Primary Workloads	Business-Critical Workloads	Consolidated Workloads
Platform Configuration							
Type	Hybrid	Hybrid	Hybrid	Hybrid	All-Flash	All-Flash	All-Flash
DRAM Memory	96 GB	192 GB	192 GB	192 GB	192 GB	192 GB	192 GB
Flash Memory	750 GB	2 TB	1.5 TB	28.2 TB	12 TB	24 TB	48 TB
Storage Capacity							
Min: Raw Capacity	26 TB	36 TB	18 TB	26 TB	12 TB	24 TB	48 TB
Max: Raw Capacity	170 TB	180 TB	162 TB	314 TB	300 TB	312 TB	336 TB
Physical							
Form Factor (Rack Units)	3U	3U	2U	2U	2U	2U	2U
Weight (Lbs)	90	90	80	80	80	80	80
Power (W)	535	535	475	475	475	475	475
Network Connections							
1 Gbps Ethernet Ports	12	12	12	12	12	12	12
1 Gbps IP-KVM Lights-out Management Port	2	2	2	2	2	2	2
Optional Connectivity	Dual-port 4/8 Fibre Channel, Dual-port 10GbE Copper/Fiber, Quad-port 1 Gbps Ethernet						
Software Services Included							
Protocols	SAN Protocol Support (iSCSI, Fibre Channel), NAS Protocol Support (NFS, CIFS, SMB 3.0)						
Data Services	De-duplication, Compression, Thin Provisioning, Snapshots, Remote Replication, Application Profiles						
Management	Web browser, SSH, IP-KVM						
Data Security	Inline 256-bit AES Encryption for Data-at-Rest						
Redundancy	No single point of failure, Active-Active High Availability Architecture						
Warranty							
Basic	24x7 support via email and phone, next business day hardware replacement for defective parts and software updates for first 90 days.						
Optional	See IntelliCare Support Program for more information						

Intelligent Flash Storage Arrays

Model	ESH-20	ESH-25	ESH-35	ESH-65	ESF-10	ESF-25	ESF-50	ESF-145
Platform Configuration								
Flash Memory	1.5 TB	750 GB	2.0 TB	2.0 TB	12 TB	24 TB	48 TB	144 TB
Storage Capacity								
Raw Capacity	18 TB	26 TB	36 TB	64 TB	12 TB	24 TB	48 TB	144 TB
Typical Usable Capacity with Compression	2x	2x	2x	2x	2x	2x	2x	2x
Typical Usable Capacity with Compression and De-Duplication	3-5x	3-5x	3-5x	3-5x	3-5x	3-5x	3-5x	3-5x
Physical								
Form Factor (Rack Units)	2U	3U	3U	4U	2U	2U	2U	4U
Weight (Lbs)	50	70	70	110	50	50	50	105
Power (W)	225	225	225	675	107	107	107	760
Array Compatibility								
T3100/3200/3300	✓	✓	✓	✓				
T3400	✓	✓	✓	✓	✓	✓	✓	✓
T3600/3700/3800	✓	✓	✓	✓	✓	✓	✓	✓

